- Smart Switching
- Fully Configurable
- Simple Integration
- Rugged Tactile Buttons
- 24-bit Backlit RGB LED's



SELECT SERIES - SMART SWITCHING. RUGGED BUILD. LIMITLESS CONTROL.

The Select Series CANKeypad puts you in control with compact, LED-backlit tactile buttons, suitable for any CAN-based application. Use it as a stand-alone switch panel, an annunciator, or alongside an Enovation Controls display.


Configuration is easy with a simple CAN protocol. Each button supports programmable RGB backlighting and status LEDs with full control of color, brightness, and flash rate, including bar graph capabilities. Built to last, and tested over 1 million cycles the keypad is IP67 rated with an integrated gasket and mounts to a panel using two M3 bolts. Four color-coded flying leads provide CAN and power connectivity, offering maximum install flexibility.






SK51

DIMENSIONS



MOUNTING TEMPLATE.
3.4mm HOLES FOR MOUNTING, 30mm HOLE FOR WIRE PASS THROUGH Cut out RED circles, BLUE square is over all outer dimensions of Keypad.



SPECIFICATIONS

OPERATING TEMPERATURE

SEALING

MOUNTING

ELECTRICAL	
OPERATING VOLTAGE	6 to 35 VDC
CURRENT CONSUMPTION	5 – 200mA (based on LED color/brightness)
MECHANICAL & ENVIRONMENTAL	
MECHANICAL & ENVINC	INIVIENTAL
CASE MATERIAL	High impact PBT/PC (epoxied)

-40°F to 185°F (-40°C to 85°C)

IP67 front, exposed lead ends

Panel mount with two M3 bolts

CAN PROTOCOL	
STANDARD	SAE J1939 compatible protocol
TRANSMIT	Button status on press/release or 1s interval
RECEIVE - SIMPLE MODE	Set backlight & status LED colors, brightness, and flash
RECEIVE - FULL RGB	24-bit RGB per LED (16M+ colors)
CAN TERMINATION	Not Fitted

▲ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

FOR MODEL & PART INFORMATION

FOR MANUAL & SUPPORT DOCUMENTS

FOR SUPPORT & WARRANTY

ENOVATIONCONTROLS.COM/SK51

SUPPORT.ENOVATIONCONTROLS.COM

ENOVATIONCONTROLS.COM/SUPPORT

SALES CONTACT



CONTACT

sales@enovationcontrols.com +1 918.317.4100

www.enovation controls.com

CORPORATE HEADQUARTERS

5311 S 122nd E Ave Tulsa, Oklahoma, USA 74146

 $\textit{United States} \cdot \textit{United Kingdom} \cdot \textit{India} \cdot \textit{China}$



FM 28221 (Tulsa, OK-USA) FM 29422 (UK)